

PCT

WELTOORGANISATION FÜR GEISTIGES EIGENTUM
Internationales Büro



INTERNATIONALE ANMELDUNG VERÖFFENTLICHT NACH DEM VERTRAG ÜBER DIE
INTERNATIONALE ZUSAMMENARBEIT AUF DEM GEBIET DES PATENTWESENS (PCT)

(51) Internationale Patentklassifikation ⁷ : B65H 35/00	A1	(11) Internationale Veröffentlichungsnummer: WO 00/58193 (43) Internationales Veröffentlichungsdatum: 5. Oktober 2000 (05.10.00)
--	-----------	---

(21) Internationales Aktenzeichen: PCT/IB00/00350	(81) Bestimmungsstaaten: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO Patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), eurasisches Patent (AM/ AZ, BY, KG, KZ, MD, RU, TJ, TM), europäisches Patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI Patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
(22) Internationales Anmeldedatum: 27. März 2000 (27.03.00)	
(30) Prioritätsdaten: 572/99 25. März 1999 (25.03.99) CH	
(71) Anmelder (für alle Bestimmungsstaaten ausser US): RAY TECHNOLOGY GROUP B.V. [NL/NL]; Albert Einsteinweg 10, NL-5151 DL Drunen (NL).	
(72) Erfinder; und	
(75) Erfinder/Anmelder (nur für US): DE REGT, Jeroen [NL/NL]; Heischeuthof 4, NL-5345 VP Oss (NL), DE MAN, Eelco, H. [NL/NL]; Ridderstraat 14, NL-5707 VP Helmond (NL).	
(74) Anwalt: SPIERENBURG, Pieter; Spierenburg Helmle-Kolb & Partner AG, Mellingerstrasse 12, CH-5443 Niederrohrdorf (CH).	

(54) Title: DEVICE FOR DISPENSING ADHESIVE TAPE IN STRIPS	
(54) Bezeichnung: VORRICHTUNG ZUR STREIFENWEISEN ABGABE VON KLEBBAND	
(57) Abstract	
<p>The invention relates to a novel device (1) for dispensing adhesive tape or similar in strips. The device is provided with a receptacle for a roll of adhesive tape (30), at least one feed roller (22; 23) which has a ring groove (48; 51) and a bending roller (47) which works together with the feed roller and has a ring protrusion (52). A first toothed bar (14) which is connected to a lever (8) and which drives the feed roller (22; 23) is also provided, together with a cutting element (33). Said cutting element can be triggered by a second toothed bar (14') which is connected to the lever (8), using a first gear wheel (38). The two toothed bars (14, 14') are provided on both sides of the lever (8). At least one of the toothed bars (14, 14') is also guided in a lower connecting link (20) which is situated in the lower area of the housing (2) and in an upper connecting link (13) which is located on the lever (8), in such a way that the toothed bar (14, 14') indirectly engages with the feed roller (22; 23) and the first gear wheel (38) during the downward movement of the lever (8) and disengages during the upward movement thereof.</p>	